

ケイカルエース・スパー・シリカ体積表

カパー 単位:m³/本

分割数	呼び径		内径 mm	厚さ(mm)				
	A	B		30	40	50	65	75
2	15	1/2	22	0.0030	0.0048	0.0069	0.0108	0.0139
	20	3/4	27	0.0033	0.0051	0.0074	0.0115	0.0147
	25	1	34	0.0037	0.0057	0.0080	0.0123	0.0157
	32	1 1/4	43	0.0042	0.0064	0.0089	0.0134	0.0170
	40	1 1/2	49	0.0045	0.0068	0.0095	0.0142	0.0178
	50	2	61	0.0052	0.0077	0.0106	0.0157	0.0195
	65	2 1/2	76	0.0061	0.0089	0.0121	0.0176	0.0217
	80	3	89	0.0068	0.0099	0.0133	0.0192	0.0236
	90	3 1/2	102	0.0076	0.0109	0.0146	0.0208	0.0254
	100	4	114	0.0083	0.0118	0.0157	0.0223	0.0272
	125	5	140	0.0098	0.0138	0.0182	0.0255	0.0309
	150	6	165	0.0112	0.0157	0.0206	0.0286	0.0345
175	7	194	0.0129	0.0179	0.0234	0.0322	0.0386	
3	200	8	216	0.0141	0.0196	0.0255	0.0350	0.0418
	225	9	245		0.0218	0.0283	0.0386	0.0460
4	250	10	267	0.0171	0.0235	0.0304	0.0413	0.0491
	275	11	300		0.0260	0.0335	0.0454	0.0539
	300	12	319	0.0201	0.0275	0.0353	0.0478	0.0566
6	350	14	356	0.0222	0.0303	0.0389	0.0524	0.0619
	400	16	406	0.0251	0.0342	0.0437	0.0586	0.0691
	450	18	457	0.0280	0.0381	0.0486	0.0650	0.0764
8	500	20	508	0.0309	0.0420	0.0534	0.0713	0.0838
	550	22	559	0.0338	0.0459	0.0583	0.0777	0.0911
	600	24	610	0.0365	0.0498	0.0632	0.0840	0.0984
	650	26	660	0.0396	0.0536	0.0680	0.0903	0.1056
12	700	28	711		0.0575	0.0729	0.0966	0.1129
	750	30	762		0.0614	0.0778	0.1030	0.1202
	800	32	813	0.0484	0.0654	0.0826	0.1093	0.1276
	850	34	864		0.0693	0.0875	0.1157	0.1349
	900	36	915		0.0732	0.0924	0.1220	0.1421
950	38	966			0.0972	0.1284	0.1496	

注)カパー及びホートのダンボール箱の寸法は405×579×626mmとする。

ANSI及び2層用カパー 単位:m³/本

分割数	呼び径		内径 mm	厚さ(mm)					
	A	B		30	40	50	65	75	
2	150	A6	170	0.0115	0.0161	0.0211	0.0293	0.0352	
3	200	A8	220	0.0144	0.0199	0.0259	0.0355	0.0424	
4	250	A10	273	0.0174	0.0240	0.0309	0.0421	0.0500	
	300	A12	324	0.0203	0.0279	0.0358			
6	2層目用						0.0484	0.0573	
				367	0.0228	0.0312	0.0399	0.0538	0.0635
				419		0.0356	0.0449		0.071
				425		0.0356	0.0455		0.0718
				469					0.0781

R付ホート 単位:m³/枚

呼び径	適用範囲	厚さ(mm)				
		30	40	50	65	75
950F	915~980	0.0055	0.0073			
1000F	981~1150	0.0055	0.0073		0.0119	
39B				0.0092		0.0137
1250F	1151~1350	0.0055	0.0073		0.0119	
47B				0.0092		0.0137
1500F	1351~1800	0.0055	0.0073		0.0119	
59B				0.0092		0.0137
2000F	1801~2700	0.0055	0.0073			
79B				0.0092	0.0119	0.0137
3000F	2701~3800	0.0055	0.0073	0.0092	0.0119	
118B				0.0092		0.0137
4000F	3801~4900	0.0055	0.0073	0.0092	0.0119	0.0137
158B				0.0092	0.0119	0.0137
5000F	4901~7000	0.0055	0.0073	0.0092	0.0119	0.0137
197B				0.0092	0.0119	0.0137

ホート 単位:m³/枚

幅×長さ	厚さ(mm)					
	25	30	40	50	65	75
150×610	0.0023	0.0027	0.0037	0.0046	0.0059	0.0069
303×610	0.0046	0.0055	0.0073	0.0092	0.0119	0.0137